

Calliper List Smurfit Kappa Graphic Board - Wrexen PM2

Foudrinier PM2	Grey		Brown		White			Black
Quality	2/glazed	Haupt Special	2/s Testliner	2/s Kraftliner	1/s white	2/s white	Coated Plus	1/s black
Density g/dm ³	630*	730	650	650	650	670	670	650
Calliper mm	Grammage g/m ²		Grammage g/m ²		Grammage g/m ²			Gramma
0,8	520							
0,9	585							
1,0 M	650				650	670		650
1,1	715				715	735		715
1,2 M	755*		780	780	780	805	805	780
1,3	820		845	845	845	870	870	845
1,4	880		910	910	910	940	940	910
1,5 M	945		975	975	975	1005	1005	975
1,6	1010		1040	1040	1040	1070	1070	1040
1,7	1070		1105	1105	1105	1140	1140	1105
1,8	1135		1170	1170	1170	1205	1205	1170
1,9	1195		1235	1235	1235	1275	1275	1235
2,0 M	1260	1460	1300	1300	1300	1340	1340	1300
2,1	1325			1365	1365		1405	1365
2,2 M	1385			1430	1430		1475	1430
2,3	1450			1495	1495		1540	1495
2,4	1510			1560	1560		1610	1560
2,5 M	1575	1825		1625	1625		1675	1625
2,6	1640			1690	1690		1740	1690
2,7	1700			1755	1755		1810	1755
2,8	1765			1820	1820		1875	1820
2,9	1830			1885	1885		1945	1885
3,0 M	1890	2190		1950	1950		2010	1950
3,1	1955							
3,2	2015							
3,3	2080							
3,4	2140							
3,5 M	2205							
3,6	2270							
3,7	2330							
3,8	2395							
3,9	2455							
4,0 M	2520							

*<1,2 mm monocapa 0,65 g/cm³

↳ 2,1 mm duplex

Large Sheets	Inline cut board machine:	min. 45,0 x 60,0 cm / max. 230,0 x 160,0 cm
Cut Pieces	Rotary cutter:	min. 8,5 x 12,5 cm / max. 137,0 x 70,0 cm
	Tolerances:	Size: +/- 0,5 mm; Angle: 3 mm/m
Packaging	One-way-pallets, max. 1250 kg, height 150-180 cm, shrink-wrapped in recyclable PE	
Quantities	Minimum quantity per quality and specification 2 to - depending on production program	
Tolerances	Calliper and grammage: +/- 5%; Large Sheets: +/- 2,0 mm	
Others	Sizes preferably to match machine trim of 230 cm Payment basis are the grammages here above, not the density.	
Samples	On Request; M = Standard, always available	

Further technical information on request. Grammages subject to variation.



2/black
670
Weight g/m ²
670
735
805
870
940
1005
1070
1140
1205
1275
1340
1405
1475
1540
1610
1675
1740
1810
1875
1945
2010

cm
cm
E-foil
lamme